







High Fault
Short Circuit
Withstand Rating
100,000A 600VAC

Contactor Cat No. 2 & 3 Pole	Max FLA	Max. Class J Non-Time Delay Fuse
C25D__15	15	60
C25D__25	25	100
C25D__30	30	100
C25D__40	40	100
C25D__50	50	200

U_i=690V / U_{imp}=6kV

30 FLA, 40 A. RES / POLE WX 120825

Volts	Locked Rotor Amps	1Ø, 1 Pole		3Ø, 3 Pole	
		HP	kW	HP	kW
115	180	2	1.5	---	---
230	180	5	3.7	10	7.5
460	150	---	---	15	11
575	120	---	---	15	11

herm.refrig.comp.

Made in China

DC RATINGS	FLA	HP	DC-5 (le)
240 V 3P IN SERIES	---	---	---
120 V 3P IN SERIES	---	---	---
120 V 2P IN SERIES	5.5	1/2	5.5
120 V PER POLE	2	1/10	2
24 V PER POLE	15	---	15

LIGHTING	IEC / EN60947 (le)			
TUNGSTEN & BALLEST	AC-1	40	@ 600 VAC	
40A PER POLE 480 VAC MAX	AC-3	30	@ 600 VAC	
	AC-4	30	@ 480 VAC	
	AC-8a	30	@ 600 VAC	

RoHS







